



IS standard



GROWING TOGETHER

# EARTHMAX

RADIAL OTR TIRES

## SR 55 M



PRODUCT DATA SHEET

# EARTHMAX SR 55 M

RADIAL OTR TIRES



EARTHMAX SR 55 M is an All-Steel radial tire specifically engineered for wheel loaders and load haul dumps (LHD) operating in the most demanding underground mining and recycling environments. Thanks to the redesigned tread wear indicator - now integrated into the circumferential grooves - the tire features a fully-closed, smooth tread pattern that significantly enhances resistance to damage and extends the tire's service life. The extra tread depth further ensures that EARTHMAX SR 55 M delivers exceptional durability and minimizes the risk of cuts and tears, even in the harshest working conditions.

- Radial
- L-5S
- A2
- 188

**Technologies**



**Performance**



	Tire size	Type	TRA CODE	STAR RATING	LI/SS	Version	TKPH	O.W.	O.D.	SLR	RC	TREAD DEPTH (mm)	RIM	
								(mm)	(mm)	(mm)	(mm)		Rec.	Alt.
Ø 25"	17.5 R 25	TL	L-5S	***	188 A2	CRC	-	455	1400	630	4211	68	14.00/1.5	-

CRC: Cut Resistance Compound



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference