


AGRIMAX RT 657

| | |
|---------------------|--|
| TIRE SIZE | 600/65 R 34 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | SKÖRDEMASKIN FÖR VINGÅRD / TRAKTOR / SKÖRDEMASKIN |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 157 D ; 160 AB |



DIMENSIONER US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA CODE | 94032327 | RC (IN) | 195.3 |
| SW (IN) | 24.1 | RIM REC | DW 20 B |
| OD (IN) | 64.7 | RIM ALT | W 18 L |
| SLR (IN) | 29.2 | ECE | E4-106R-001405 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 |
|-----------|------|------|------|------|------|-------|-------|-------|
| 40 | 4360 | 5090 | 5730 | 6370 | 7010 | 7550 | 8370 | 9100 |
| 30 | 4600 | 5360 | 6030 | 6690 | 7360 | 7940 | 8800 | 9560 |
| 25 | 4760 | 5560 | 6250 | 6940 | 7640 | 8230 | 9130 | 9920 |
| 20 | 5030 | 5860 | 6590 | 7330 | 8060 | 8690 | 9630 | 10460 |
| 5 LT | 5850 | 6830 | 7680 | 8540 | 9390 | 10120 | 11220 | 12190 |
| 5 HT | 5030 | 5860 | 6590 | 7330 | 8060 | 8690 | 9630 | 10460 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.