


AGRIMAX V- FLECTO

TIRE SIZE	VF 650/65 R 42
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ТРАКТОР ВЫСОКОЙ МОЩНОСТИ / ТРАКТОР-ТЯГАЧ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	174 D



РАЗМЕРЫ US STANDARD

USA CODE	94062102	RC (IN)	227.3
SW (IN)	25.6	RIM REC	DW 23 B
OD (IN)	75.3	RIM ALT	DW 21 B
SLR (IN)	33.5	ECE	E11-106R-005713

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
45	6840	7910	8990	10210	11140	12090	13440
FROM 40 TO 25	7530	8710	9890	11220	12260	13290	14770
20	7670	8870	10070	11440	12500	13560	15060
12	7830	9050	10270	11660	12740	13820	15350
5	8280	9580	10870	12330	13480	14620	16250
*UPTO 5 CYC WITH FRONT LOADER	10540	12190	13830	15710	17150	18610	20680
5 HT	7670	8870	10070	11440	12500	13560	15060

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.