

FLOTATION 558

TIRE SIZE	500/45 - 22.5
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	EMPACADORA DE HENO / COSECHADORA / CAMIÓN CISTERNA / REMOLQUE / COSECHADORA / MAQUINARIA AGRÍCOLA
VERSIÓN	ARAMID BELTED HD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	142 A8/138 B
LI/SS FREE ROLLING	154 A8/150 B



DIMENSIONES US STANDARD

CÓDIGO USA	94048281	RC (IN)	124.7
SW (IN)	19.7	RIM REC	AG 16.00
OD (IN)	41.1	ECE	E11-106R-005352
SLR (IN)	18.5	PR	16

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	46	49	52
5 FR	10800	11190	11570
10 FR	9720	10070	10420
20 FR	8640	8950	9260
25 FR	7720	7990	8270
30 FR	6940	7200	7390
5 DW	7640	7910	8180
10 DW	6880	7120	7360
20 DW	6110	6340	6550
25 DW	5460	5650	5840
30 DW	4920	5090	5200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.