

AGRIMAX V-FLECTO

TYRE SIZE	VF 650/60 R 42
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	HIGH-POWER TRACTOR / TRACTOR
VERSION	STANDARD
TL/TT	TL
LI/SS	174 D



DIMENSIONS US STANDARD

USA CODE	94074808	RC (IN)	219.1
SW (IN)	26.0	RIM REC	DW 23 B
OD (IN)	72.6	RIM ALT	DW21B
SLR (IN)	32.8	ECE	E11-106R-008774

LOAD CAPACITY (LBS/TYRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	6170	7120	8190	9130	10210	11140	12490	13440
FROM 40 TO 25	6790	7830	9010	10040	11220	12260	13730	14770
20	6920	7970	9180	10230	11440	12490	14000	15060
12	7050	8130	9360	10440	11660	12740	14270	15350
5	7470	8610	9910	11040	12350	13480	15100	16250
*UPTO 5 CYC WITH FRONT LOADER	9500	10960	12610	14050	15710	17160	19220	20680
5 HT	6920	7970	9180	10230	11440	12490	14000	15060

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.