

# PL 801

<b>TIRE SIZE</b>	<b>6.00 - 9</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	РОТОРНЫЕ ГРАБЛИ / СЕНОВОРОШИЛКА / КОМБАЙН / ВИЛОЧНЫЙ ПОГРУЗЧИК / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ВИЛОЧНЫЙ ПОГРУЗЧИК
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TT



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	157	<b>PR</b>	12
<b>OD (MM)</b>	543		
<b>RIM REC</b>	4.00 E		
<b>ECE</b>	E11-106R-003565		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	10.00
25 LOAD WHEEL	1885
25 STEER WHEEL	1450
10 OTHER VEHICLES	1885
25 OTHER VEHICLES	1450
STATIC SIDE LOADER	2190

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.