

# EARTHMAX SR 402

|                     |                        |
|---------------------|------------------------|
| <b>TIRE SIZE</b>    | 16.00 R 25             |
| <b>UM</b>           | IS STANDARD            |
| <b>CONSTRUCTION</b> |                        |
| <b>MACHINERY</b>    | RIGID DUMP TRUCK       |
| <b>VERSION</b>      | CUT RESISTANT COMPOUND |
| <b>TIRE TYPE</b>    | TL                     |
| <b>LI/SS</b>        | 183 B                  |



## DIMENSIONS IS STANDARD

|                 |           |                    |     |
|-----------------|-----------|--------------------|-----|
| <b>OD (MM)</b>  | 1520      | <b>TRA CODE</b>    | E4  |
| <b>SLR (MM)</b> | 694       | <b>STAR RATING</b> | ★★★ |
| <b>RC (MM)</b>  | 4640      |                    |     |
| <b>RIM REC</b>  | 11.25/2.0 |                    |     |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 7.50 | 8.00 | 8.50 | 9.00 |
|------------|------|------|------|------|
| 50         | 7500 | 8000 | 8250 | 8750 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.