

# AGRIMAX PROHARVEST

<b>TIRE SIZE</b>	<b>VF 620/70 R 26</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	
<b>MACHINERY</b>	HARVESTER
<b>VERSION</b>	STEEL BELTED
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	173 D



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	620	<b>RIM REC</b>	DW 21 B
<b>OD (MM)</b>	1528	<b>RIM ALT</b>	DW 20 B; DW 23 B
<b>SLR (MM)</b>	670	<b>ECE</b>	E11-106R-0011721
<b>RC (MM)</b>	4590	<b>SRI</b>	725

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1	1.2	1.4	1.6	2	2.4	2.8
70	2545	2960	3375	3790	4200	4615	5090	5385	5915
<b>FROM 65 TO 40</b>	2795	3250	3705	4160	4615	5070	5590	5915	6500
30	2855	3315	3780	4245	4710	5175	5705	6035	6630
20	2910	3380	3855	4330	4800	5275	5815	6155	6760
10	3075	3575	4080	4580	5080	5580	6150	6510	7150
<b>*UPTO 30 CYC</b>	3175	3690	4210	4725	5240	5760	6350	6720	7380
<b>*UPTO 15 CYC</b>	3790	4405	5025	5640	6260	6875	7580	8020	8810
<b>*UPTO 10 CYC</b>	4155	4830	5505	6180	6860	7535	8305	8790	9655
10HT	2855	3315	3780	4245	4710	5175	5705	6035	6630

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.