

# FLOTATION 648

<b>TYRE SIZE</b>	<b>500/50 - 22.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	HAY HARVESTER / IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TYRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	151 A8/147 B
<b>LI/SS FREE ROLLING</b>	163 A8/159 B



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94037827	<b>RC (IN)</b>	126.0
<b>SW (IN)</b>	19.7	<b>RIM REC</b>	AG 16.00
<b>OD (IN)</b>	42.1	<b>ECE</b>	E11-106R-003400
<b>SLR (IN)</b>	18.7	<b>PR</b>	20

## LOAD CAPACITY (LBS/TYRE)

MPH / PSI	49	52	55
<b>5 FR</b>	14110	14580	15050
<b>10 FR</b>	12700	13130	13550
<b>20 FR</b>	11290	11660	12040
<b>25 FR</b>	10070	10420	10750
<b>30 FR</b>	9070	9380	9640
<b>5 DW</b>	9990	10330	10650
<b>10 DW</b>	8980	9290	9580
<b>20 DW</b>	7990	8260	8520
<b>25 DW</b>	7130	7370	7610
<b>30 DW</b>	6420	6640	6780

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.