


AGRIMAX V- FLECTO

TIRE SIZE	VF 710/75 R 42
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTOR DE ALTA POTENCIA / TRACTOR
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS	184 D



DIMENSIONES IS STANDARD

SW (MM)	730	RIM REC	DW 24 B
OD (MM)	2150	RIM ALT	DW 23 B; DW 25 B
SLR (MM)	937	ECE	E11-106R-009074
RC (MM)	6412	SRI	1000

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0
70	4095	4750	5405	6140	6795	7450	8190
FROM 65 TO 40	4500	5220	5940	6750	7470	8190	9000
30	4590	5320	6055	6885	7615	8350	9180
20	4680	5425	6175	7020	7765	8515	9360
10	4950	5740	6530	7425	8215	9005	9900
*UPTO 10 CYC WITH FRONT LOADER	6300	7305	8315	9450	10455	11465	12600
10 HT	4590	5320	6055	6885	7615	8350	9180

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.