

AGRIMAX RT 855

TIRE SIZE	420/80 R 50
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	SPRAYER / VINEYARD HARVESTER / TRACTOR / HARVESTER / IMPLEMENTS
VERSION	STEEL BELTED
TL/TT	TL
LI/SS	165 A8/B



DIMENSIONS IS STANDARD

SW (MM)	418	RIM REC	W 13
OD (MM)	1951	RIM ALT	W 12
SLR (MM)	915	ECE	E11-106R-0010078
RC (MM)	5955	SRI	950

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4
50	2215	2475	2785	3040	3350	3555	3915	4225	4485	4740	5150
40	2215	2475	2785	3040	3350	3555	3915	4225	4485	4740	5150
30	2375	2650	2980	3255	3585	3810	4195	4525	4800	5075	5515
10 LT	2970	3315	3730	4075	4490	4765	5250	5665	6010	6355	6905
10 HT	2375	2650	2980	3255	3585	3810	4195	4525	4800	5075	5515

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.