


# AS 504

<b>TIRE SIZE</b>	<b>19.0/45 - 17</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	ELEVADOR TELESCÓPICO / EWMOLQUE PARA CAMPOS / MAQUINARIA AGRÍCOLA / ELEVADOR TELESCÓPICO
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	131 A8
<b>LI/SS FREE ROLLING</b>	144 A8



## DIMENSIONES IS STANDARD

<b>SW (MM)</b>	465	<b>RIM REC</b>	16.00
<b>OD (MM)</b>	865	<b>ECE</b>	E4-106R-001814
<b>SLR (MM)</b>	389	<b>PR</b>	14
<b>RC (MM)</b>	2578	<b>SRI</b>	410

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	2.80
10 FR	3920
25 FR	3330
30 FR	3135
40 FR	2800
10 DW	2730
25 DW	2320
30 DW	2185
40 DW	1950

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.