


# RIB 713

<b>TIRE SIZE</b>	<b>IF 320/70 R 15</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	LANDWIRTSCHAFTLICHE GERÄTE / LANDWIRTSCHAFTLICHE GERÄTE
<b>VERSION</b>	STUBBLE RESISTANT
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	146 D



## ABMESSUNGEN IS STANDARD

<b>SW (MM)</b>	320	<b>RIM REC</b>	W10
<b>OD (MM)</b>	823	<b>ECE</b>	E11-106R-003959
<b>SLR (MM)</b>	367	<b>SRI</b>	390
<b>RC (MM)</b>	2590	<b>TRA CODE</b>	I1

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	5.0	5.2
FROM 10 TO 65 KM/H	855	1090	1325	1500	1735	1970	2175	2380	2615	2935	3000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.