


# AGRIMAX FORCE



<b>TYRE SIZE</b>	<b>IF 710/60 R 34</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HIGH-POWER TRACTOR / TRACTOR
<b>VERSION</b>	SPECIAL
<b>TYRE TYPE</b>	TL
<b>LI/SS</b>	170 D

## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	708	<b>RIM REC</b>	DW 25 B
<b>OD (MM)</b>	1716	<b>ECE</b>	E4-106R-001485
<b>SLR (MM)</b>	763	<b>SRI</b>	825
<b>RC (MM)</b>	5126	<b>TRA CODE</b>	R1W

## LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
<b>70</b>	2510	2890	3330	3710	4145	4530	5075	5460
<b>FROM 65 TO 40</b>	2760	3180	3660	4080	4560	4980	5580	6000
<b>30</b>	2870	3305	3805	4240	4740	5175	5800	6240
<b>20</b>	2980	3430	3950	4405	4920	5375	6025	6420
<b>10</b>	3505	4035	4645	5180	5790	6320	7085	7625
<b>UPTO 30 CYC</b>	3585	4130	4755	5300	5925	6470	7250	7800
<b>UPTO 15 CYC</b>	4275	4925	5670	6320	7065	7715	8645	9300
<b>UPTO 10 CYC</b>	4690	5405	6220	6935	7750	8465	9485	10200
<b>10 HT</b>	2870	3305	3805	4240	4740	5175	5800	6240

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.