


AGRIMAX TERIS

| | |
|---------------------|--|
| TYRE SIZE | IF 710/75 R 32 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| VERSION | STANDARD |
| TYRE TYPE | TL |
| LI/SS | 183 A8/B |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 716 | RIM REC | DW 25 B |
| OD (MM) | 1879 | RIM ALT | DW 23 B |
| SLR (MM) | 851 | ECE | E11-106R-005025 |
| RC (MM) | 5653 | SRI | 875 |

LOAD CAPACITY (KG/TYRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.4 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 |
|------------|------|------|------|-------|-------|-------|-------|-------|-------|
| 50 | 3415 | 4025 | 4640 | 5775 | 6300 | 6915 | 7440 | 8140 | 8750 |
| 40 | 3415 | 4025 | 4640 | 5775 | 6300 | 6915 | 7440 | 8140 | 8750 |
| 30 | 3655 | 4310 | 4965 | 6185 | 6745 | 7400 | 7965 | 8710 | 9365 |
| 15 CYC* | 5295 | 6240 | 7190 | 8955 | 9770 | 10720 | 11535 | 12620 | 13565 |
| 10 CYC* | 6145 | 7245 | 8350 | 10395 | 11340 | 12445 | 13390 | 14650 | 15750 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.