


MULTIMAX MP 522



| | |
|---------------------|------------------------------------------------------------------------------------------|
| | 480/80 R 26 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | KÜÇÜK YÜKLEYİCİ / TELESKOPIK YÜKLEYİCİ / KÜÇÜK YÜKLEYİCİ / TELESKOPIK YÜKLEYİCİ |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| | 160 A8/B |

UNDEFINED US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94052707 | RC (IN) | 168.8 |
| SW (IN) | 18.9 | RIM REC | DW 15 L |
| OD (IN) | 56.2 | RIM ALT | DW 16 L |
| SLR (IN) | 25.1 | ECE | E11-106R-002970 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 23 | 29 | 32 | 35 | 38 | 41 | 44 | 46 | 49 | 52 |
|---------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30 | 5750 | 6750 | 7340 | 7840 | 8330 | 8830 | 9420 | 9920 | - | - |
| 25 | 5750 | 6750 | 7340 | 7840 | 8330 | 8830 | 9420 | 9920 | - | - |
| 20 | 6160 | 7220 | 7860 | 8390 | 8920 | 9460 | 10090 | 10610 | - | - |
| 15 | 6390 | 7500 | 8160 | 8710 | 9260 | 9810 | 10470 | 11010 | - | - |
| 5 CYC. | 7000 | 8630 | 9380 | 10120 | 11010 | 11760 | 12500 | 13390 | 14140 | 14880 |
| STATIC | 10720 | 13240 | 14380 | 15520 | 16890 | 18030 | 19170 | 20530 | 21680 | 22820 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.