

# AW 705

<b>TIRE SIZE</b>	<b>14.0/65 - 16</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	EMPACADORA DE HENO / MAQUINARIA AGRÍCOLA / REMOLQUE / COSECHADORA / MAQUINARIA AGRÍCOLA
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS FREE ROLLING</b>	142 A8



## DIMENSIONES US STANDARD

<b>CÓDIGO USA</b>	94009930	<b>RC (IN)</b>	100.4
<b>SW (IN)</b>	13.9	<b>RIM REC</b>	11.0
<b>OD (IN)</b>	34.3	<b>ECE</b>	E4-106R-001901
<b>SLR (IN)</b>	15.3	<b>PR</b>	14

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>58</b>
<b>5 FR</b>	8180
<b>15 FR</b>	6960
<b>20 FR</b>	6550
<b>25 FR</b>	5840

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.