


RIDEMAX FL 693 M



	650/55 R 26.5
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TANKER / RÖMORK / UYGULAMALI MAKINE
VERSION	HD
TIRE TYPE	TL
	178 D

UNDEFINED US STANDARD

USA CODE	94049622	RC (IN)	167.3
SW (IN)	25.4	RIM REC	AG 20.00
OD (IN)	54.7	ECE	E11-106R-003008
SLR (IN)	24.2		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	15	17	23	29	35	41	46	52	58	73	87
40	5130	6120	7440	8600	9920	11240	12070	13390	14720	15540	16530
30	6210	7410	9010	10410	12000	13610	14600	16210	17810	18820	20010
25	6980	8320	10120	11690	13490	15300	16420	18220	20020	21140	22490
20	7750	9250	11240	12980	14980	16990	18230	20230	22220	23480	24970
15	8100	9670	11760	13590	15670	17770	19080	21160	23260	24560	26120
5	9230	11010	13390	15480	17860	20240	21730	24110	26490	27980	29760

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.