

# AS 504

7.00 - 12

|              |                                                                                       |
|--------------|---------------------------------------------------------------------------------------|
| UM           | US STANDARD                                                                           |
| CONSTRUCTION | BIAS                                                                                  |
| MACHINERY    | TELESKOPIK YÜKLEYİCİ / TARLA<br>RÖMORKU / UYGULAMALI MAKİNE /<br>TELESKOPIK YÜKLEYİCİ |
| VERSION      | STANDARD                                                                              |
| TIRE TYPE    | TL                                                                                    |
|              | 83 A8                                                                                 |
|              | 95 A8                                                                                 |



## UNDEFINED US STANDARD

|          |          |         |                |
|----------|----------|---------|----------------|
| USA CODE | 94019274 | RC (IN) | 80.7           |
| SW (IN)  | 7.4      | RIM REC | 4.5            |
| OD (IN)  | 26.9     | ECE     | E4-106R-001956 |
| SLR (IN) | 12.2     | PR      | 6              |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 36   |
|-----------|------|
| 5 FR      | 2130 |
| 15 FR     | 1810 |
| 20 FR     | 1710 |
| 25 FR     | 1520 |
| 5 DW      | 1500 |
| 15 DW     | 1270 |
| 20 DW     | 1200 |
| 25 DW     | 1070 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.