DATA SHEET

PRINTED ON
23-04-2026

PL 801

TIRE SIZE	**5.00 - 8**
UM	US STANDARD
CONSTRUCTION	BIAS
MACHINERY	RASTRILLO HILERADOR ROTATIVO / COSECHADORA / CARRETILLA ELEVADORA / COSECHADORA / MAQUINARIA AGRÍCOLA / CARRETILLA ELEVADORA
VERSIÓN	STANDARD
TIRE TYPE	TT

DIMENSIONES US STANDARD

CÓDIGO USA	94007103	**RIM ALT**	3.25 I
SW (IN)	5.3	**ECE**	E11-106R-003381
OD (IN)	18.4	**PR**	8
RIM REC	3.00 D		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	120
15 LOAD WHEEL	2725
15 STEER WHEEL	2095
5 OTHER VEHICLES	2725
15 OTHER VEHICLES	2095
STATIC SIDE LOADER	3165

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..