


# AGRIMAX FORCE



<b>TIRE SIZE</b>	<b>IF 710/60 R 34</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	MAȘINĂ DE RECOLTARE / TRACTOR DE MARE PUTERE / TRACTOR
<b>VERSION</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	170 D

## DIMENSIUNI IS STANDARD

<b>SW (MM)</b>	708	<b>RIM REC</b>	DW 25 B
<b>OD (MM)</b>	1716	<b>ECE</b>	E4-106R-001485
<b>SLR (MM)</b>	763	<b>SRI</b>	825
<b>RC (MM)</b>	5126	<b>TRA CODE</b>	R1W

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	2510	2890	3330	3710	4145	4530	5075	5460
<b>FROM 65 TO 40</b>	2760	3180	3660	4080	4560	4980	5580	6000
30	2870	3305	3805	4240	4740	5175	5800	6240
20	2980	3430	3950	4405	4920	5375	6025	6420
10	3505	4035	4645	5180	5790	6320	7085	7625
<b>UPTO 30 CYC</b>	3585	4130	4755	5300	5925	6470	7250	7800
<b>UPTO 15 CYC</b>	4275	4925	5670	6320	7065	7715	8645	9300
<b>UPTO 10 CYC</b>	4690	5405	6220	6935	7750	8465	9485	10200
10 HT	2870	3305	3805	4240	4740	5175	5800	6240

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.