


# AGRIMAX RT 765

<b>TYRE SIZE</b>	<b>420/70 R 28</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR / IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TYRE TYPE</b>	TL
<b>LI/SS</b>	133 D



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94062171	<b>RC (IN)</b>	158.3
<b>SW (IN)</b>	16.5	<b>RIM REC</b>	W 13
<b>OD (IN)</b>	53.1	<b>RIM ALT</b>	W 12; W 14 L
<b>SLR (IN)</b>	23.8	<b>ECE</b>	E11-106R-005520

## LOAD CAPACITY (LBS/TYRE)

MPH / PSI	9	12	15	17	20	23
40	2500	2910	3320	3730	4130	4540
30	2630	3060	3490	3920	4350	4770
25	2740	3200	3640	4090	4540	4980
20	2880	3350	3820	4290	4760	5220
5 LT	3360	3900	4450	5000	5560	6100
5 HT	2880	3350	3820	4290	4760	5220

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.