


AGRIMAX SIRIO

TIRE SIZE	540/65 R 34
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ТРАКТОР ВЫСОКОЙ МОЩНОСТИ / ТРАКТОР-ТЯГАЧ
VERSION	HIGH SPEED
TIRE TYPE	TL
LI/SS	152 D ; 149 E



РАЗМЕРЫ US STANDARD

USA CODE	94045297	RC (IN)	186.4
SW (IN)	20.9	RIM REC	W 16 L
OD (IN)	61.7	RIM ALT	W 18
SLR (IN)	28.4	ECE	E4-106R-000815

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	3370	3870	4440	5020	5590	6160	6670	7160
40	3680	4230	4860	5480	6110	6730	7290	7830
30	3870	4440	5100	5760	6420	7080	7650	8220
25	4030	4640	5320	6010	6690	7390	7980	8580
15	4360	5020	5760	6500	7240	7990	8640	9280
5	5520	6350	7290	8220	9160	10100	10920	11740

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.