


# EARTHMAX SR 22 AS

TIRE SIZE	20.5 R 25
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	LOADER / GRADER
VERSION	CUT RESISTANT COMPOUND
TIRE TYPE	TL
LI/SS	177 B ; 161 A8 ; 193 A2



## DIMENSIONS IS STANDARD

OD (MM)	1493	TRA CODE	E2/G2/L2
SLR (MM)	641	STAR RATING	★★/★/★★
RC (MM)	4324		
RIM REC	17.00/2.0		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.25	1.50	1.75	2.00	2.25	2.50	2.75	3.00	4.00	4.25	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25
50	-	-	-	-	-	-	-	-	5800	6150	6500	6700	6900	7300	-	-	-	-
40	2430	2800	3150	3450	3875	4125	4375	4625	-	-	-	-	-	-	-	-	-	-
10	-	-	-	-	-	-	-	-	-	-	-	-	-	9750	10000	10300	10900	11200

KM/H / BAR	6.50
50	-
40	-
10	11500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.