


# AGRIMAX RT 855

|                     |                                                                                          |
|---------------------|------------------------------------------------------------------------------------------|
|                     | <b>210/95 R 18</b>                                                                       |
| <b>UM</b>           | IS STANDARD                                                                              |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | ILAÇLAMA / ÜZÜM HASAT MAKINESİ /<br>TRAKTÖR / BIÇERDÖVER /<br>UYGULAMALI MAKINE          |
| <b>VERSION</b>      | STANDARD                                                                                 |
| <b>TIRE TYPE</b>    | TL                                                                                       |
|                     | 108 A8/B                                                                                 |



## UNDEFINED IS STANDARD

|                 |      |                |               |
|-----------------|------|----------------|---------------|
| <b>SW (MM)</b>  | 214  | <b>RIM REC</b> | W 7           |
| <b>OD (MM)</b>  | 855  | <b>RIM ALT</b> | W 6           |
| <b>SLR (MM)</b> | 385  | <b>ECE</b>     | E4-106R-00634 |
| <b>RC (MM)</b>  | 2565 | <b>SRI</b>     | 400           |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4  | 1.6  | 2.0  | 2.4  |
|------------|-----|-----|-----|-----|------|------|------|------|
| 50         | 470 | 540 | 620 | 700 | 780  | 860  | 930  | 1000 |
| 40         | 470 | 540 | 620 | 700 | 780  | 860  | 930  | 1000 |
| 30         | 505 | 580 | 665 | 750 | 835  | 925  | 1000 | 1070 |
| 10 LT      | 630 | 725 | 835 | 940 | 1050 | 1155 | 1250 | 1340 |
| 10 HT      | 505 | 580 | 665 | 750 | 835  | 925  | 1000 | 1070 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.