

RIDEMAX FL 690

TIRE SIZE	28L R 26
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	АВТОЦИСТЕРНА / ПРИЦЕП / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	176 A8 ; 173 B



РАЗМЕРЫ IS STANDARD

SW (MM)	719	RIM REC	DW 25 B
OD (MM)	1590	RIM ALT	DW 23 B
SLR (MM)	695	ECE	E11-106R-002985
RC (MM)	4745	SRI	750

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.4	1.6	2.0	2.4	2.8
50	3120	3560	4325	4680	5330	5915	6500
40	3410	3885	4725	5115	5825	6465	7100
30	3820	4355	5295	5730	6525	7240	7955
25	4060	4625	5620	6085	6930	7690	8450
10	4775	5440	6615	7160	8155	9050	9940

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.