


# AGRIMAX V- FLECTO

<b>TIRE SIZE</b>	<b>VF 650/60 R 38</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ТРАКТОР ВЫСОКОЙ МОЩНОСТИ / ТРАКТОР-ТЯГАЧ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	166 D



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94062119	<b>RC (IN)</b>	205.9
<b>SW (IN)</b>	25.6	<b>RIM REC</b>	DW 23 B
<b>OD (IN)</b>	68.7	<b>RIM ALT</b>	DW 21 B
<b>SLR (IN)</b>	30.5	<b>ECE</b>	E11-106R-005712

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
45	5840	6790	7750	8710	9670	10630
<b>FROM 40 TO 25</b>	6430	7470	8520	9580	10630	11685
20	6550	7620	8690	9770	10840	11920
12	6680	7770	8850	9950	11040	12150
5	7070	8210	9370	10530	11680	12850
<b>*UPTO 5 CYC WITH FRONT LOADER</b>	8990	10460	11930	13400	14870	16360
5 HT	6550	7620	8690	9770	10840	11920

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.