


# AW 702

<b>TIRE SIZE</b>	<b>7.00 - 12</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	EMPACADORA DE HENO / MAQUINARIA AGRÍCOLA / REMOLQUE / COSECHADORA / MAQUINARIA AGRÍCOLA / REMOLQUE
<b>VERSIÓN</b>	ARAMID BELTED
<b>TIRE TYPE</b>	TL
<b>LI/SS FREE ROLLING</b>	95 A8



## DIMENSIONES US STANDARD

<b>CÓDIGO USA</b>	94048007	<b>RC (IN)</b>	76.7
<b>SW (IN)</b>	7.3	<b>RIM REC</b>	4.25
<b>OD (IN)</b>	26.2	<b>ECE</b>	E11-106R-004243
<b>SLR (IN)</b>	11.6	<b>PR</b>	6

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>36</b>
<b>5 FR</b>	2130
<b>15 FR</b>	1810
<b>20 FR</b>	1710
<b>25 FR</b>	1520

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.