

# TR 273

|                     |                  |
|---------------------|------------------|
| <b>TIRE SIZE</b>    | <b>18.4 - 34</b> |
| <b>UM</b>           | US STANDARD      |
| <b>CONSTRUCTION</b> | BIAS             |
| <b>MACHINERY</b>    | TRAKTOR          |
| <b>VERSION</b>      | STANDARD         |
| <b>TIRE TYPE</b>    | TT               |
| <b>LI/SS</b>        | 146 A8           |



## DIMENSIONER US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94055821 | <b>RC (IN)</b> | 206.8           |
| <b>SW (IN)</b>  | 18.7     | <b>RIM REC</b> | DW 16A          |
| <b>OD (IN)</b>  | 67.0     | <b>RIM ALT</b> | W16L;W15L;DW15L |
| <b>SLR (IN)</b> | 30.5     | <b>ECE</b>     | E11-106R-004517 |

## LOAD CAPACITY (LBS/TIRE)

|                  |             |
|------------------|-------------|
| <b>MPH / PSI</b> | <b>32.0</b> |
| 25               | 6600        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.