

AW 729

| | |
|---------------------------|--|
| TIRE SIZE | 15.0/55 - 17 |
| UM | US STANDARD |
| CONSTRUCTION | ⊠ BIAS |
| MACHINERY | EMPACADORA DE HENO / MAQUINARIA AGRÍCOLA / REMOLQUE / COSECHADORA / MAQUINARIA AGRÍCOLA |
| VERSIÓN | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 122 A8 |
| LI/SS FREE ROLLING | 134 A8 |



DIMENSIONES US STANDARD

| | | | |
|-------------------|----------|----------------|-----------------|
| CÓDIGO USA | 94065387 | RC (IN) | 100.8 |
| SW (IN) | 15.2 | RIM REC | 13.00 |
| OD (IN) | 33.5 | RIM ALT | 13; W 13 |
| SLR (IN) | 14.8 | ECE | E11-106R-006434 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 38 |
|-----------|------|
| 5 FR | 6550 |
| 15 FR | 5570 |
| 20 FR | 5240 |
| 25 FR | 4680 |
| 5 DW | 4630 |
| 15 DW | 3940 |
| 20 DW | 3700 |
| 25 DW | 3300 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.