


# AGRIMAX ELOS

<b>TIRE SIZE</b>	<b>520/85 R 42</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	167 A8/B



## DIMENSIUNI US STANDARD

<b>USA CODE</b>	94075850	<b>RC (IN)</b>	240.0
<b>SW (IN)</b>	20.3	<b>RIM REC</b>	DW 16 L
<b>OD (IN)</b>	78.3	<b>RIM ALT</b>	DD 18 L; DW 18 L
<b>SLR (IN)</b>	36.2	<b>ECE</b>	E11-106R-0010146

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	14	17	20	23	29	35	41	46	52	58
30	4700	5530	6370	7100	7940	8650	9500	10460	11300	12010
25	4700	5530	6370	7100	7940	8650	9500	10460	11300	12010
20	5030	5920	6820	7590	8500	9270	10160	11200	12090	12860
5 LT	6280	7420	8540	9500	10640	11600	12730	14020	15140	16100
5 HT	5030	5920	6820	7590	8500	9270	10160	11200	12090	12860

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.