

AGRIMAX RT 765

TIRE SIZE	580/70 R 38
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ОПРЫСКИВАТЕЛЬ / ТРАКТОР-ТЯГАЧ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	155 D



РАЗМЕРЫ US STANDARD

USA CODE	94062324	RC (IN)	215.4
SW (IN)	22.7	RIM REC	W 18 L
OD (IN)	71.9	ECE	E11-106R-005526
SLR (IN)	32.3	TRA CODE	R1W

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	90	12	15	17	20	23
40	4710	5470	6240	7010	7780	8540
30	4940	5740	6560	7360	8170	8970
25	5150	6000	6830	7680	8520	9360
20	5410	6290	7190	8070	8950	9830
5 LT	6300	7330	8370	9390	10430	11450
5 HT	5410	6290	7190	8070	8950	9830

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.