


# RIDEMAX IT 696

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>340/80 R 18 IND</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | ТРАКТОР-ТЯГАЧ  |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 143 A8 ; 138 D   |



## РАЗМЕРЫ US STANDARD

|                 |          |                |                  |
|-----------------|----------|----------------|------------------|
| <b>USA CODE</b> | 94048960 | <b>RC (IN)</b> | 117.3            |
| <b>SW (IN)</b>  | 13.5     | <b>RIM REC</b> | 11; 11 SDC; W 11 |
| <b>OD (IN)</b>  | 39.4     | <b>RIM ALT</b> | W 10; 12; 12 SDC |
| <b>SLR (IN)</b> | 18.0     | <b>ECE</b>     | E11-106R-002987  |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 17   | 23   | 29   | 35   | 41   | 46   | 51   | 58   |
|-----------|------|------|------|------|------|------|------|------|
| 40        | 2030 | 2500 | 2970 | 3380 | 3850 | 4320 | 4630 | 5200 |
| 30        | 2190 | 2700 | 3210 | 3660 | 4160 | 4660 | 5000 | 5620 |
| 25        | 2350 | 2890 | 3430 | 3900 | 4440 | 4980 | 5350 | 6010 |
| 20        | 2450 | 3010 | 3580 | 4070 | 4630 | 5200 | 5570 | 6250 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.