

# PL 801

<b>TIRE SIZE</b>	<b>6.50 - 10</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊗ BIAS
<b>MACHINERY</b>	ROTTERANDE HARV / SKÖRDEMASKIN / GAFFELTRUCK / SKÖRDEMASKIN / ARBETSFORDON / GAFFELTRUCK
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TT



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94007165	<b>RIM ALT</b>	5.50 F
<b>SW (IN)</b>	7.3	<b>ECE</b>	E11-106R-003566
<b>OD (IN)</b>	23.4	<b>PR</b>	10
<b>RIM REC</b>	5.00 F		

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>112</b>
<b>15 LOAD WHEEL</b>	4300
<b>15 STEER WHEEL</b>	3305
<b>5 OTHER VEHICLES</b>	4300
<b>15 OTHER VEHICLES</b>	3305
<b>STATIC SIDE LOADER</b>	4995

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.