



PRINTED ON  
23-04-2026

## DATA SHEET

# AT 111

|                     |                     |
|---------------------|---------------------|
| <b>TIRE SIZE</b>    | <b>AT 18X10 - 9</b> |
| <b>UM</b>           | US STANDARD         |
| <b>CONSTRUCTION</b> | ⊠ BIAS              |
| <b>MACHINERY</b>    | FYRHJULING          |
| <b>VERSION</b>      | STANDARD            |
| <b>TIRE TYPE</b>    | TL                  |



### DIMENSIONER US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>USA CODE</b> | 94026852 | <b>RIM ALT</b> | 7.5 AT; 8.5 AT |
| <b>SW (IN)</b>  | 10.0     | <b>ECE</b>     | E4-75R-0006323 |
| <b>OD (IN)</b>  | 18.0     | <b>PR</b>      | 4              |
| <b>RIM REC</b>  | 8.0 AT   |                |                |

### LOAD CAPACITY (LBS/TIRE)

|                  |          |
|------------------|----------|
| <b>MPH / PSI</b> | <b>5</b> |
| 62               | 225      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.