

AGRIMAX RT 955

TIRE SIZE	270/95 R 48
UM	IS STANDARD
MACHINERY	PULVÉRISATEUR / MACHINE À VENDANGER / MOISSONNEUSE / OUTILLAGE AGRICOLE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	144 A8/B



DIMENSIONS IS STANDARD

SW (MM)	275	RIM ALT	W 8 ; W 10
OD (MM)	1733	ECE	E4-106R-000782
SLR (MM)	820	SRI	825
RC (MM)	5351	TRA CODE	R1
RIM REC	W 9	TREAD DEPTH (MM)	34,5

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4
50	1095	1430	1740	1905	2020	2215	2410	2605	2800	-
40	1095	1430	1740	1905	2020	2215	2410	2605	2800	-
30	1170	1530	1860	2040	2160	2370	2580	2790	3000	-
10	1305	1640	2020	2395	2775	2860	3195	3530	3865	4200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.