

AS 504

| | |
|---------------------------|--|
| TIRE SIZE | 19.0/45 - 17 |
| UM | US STANDARD |
| CONSTRUCTION | BIAS |
| MACHINERY | TELESKOPLADER / FELD-ANHÄNGER / LANDWIRTSCHAFTLICHE GERÄTE / TELESKOPLADER |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 131 A8 |
| LI/SS FREE ROLLING | 144 A8 |



ABMESSUNGEN US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA-CODE | 94019137 | RC (IN) | 101.5 |
| SW (IN) | 18.3 | RIM REC | 16.00 |
| OD (IN) | 34.1 | ECE | E4-106R-001814 |
| SLR (IN) | 15.3 | PR | 14 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 41 |
|-----------|------|
| 5 FR | 8640 |
| 15 FR | 7340 |
| 20 FR | 6910 |
| 25 FR | 6170 |
| 5 DW | 6020 |
| 15 DW | 5110 |
| 20 DW | 4820 |
| 25 DW | 4300 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.