

AW 729

| | |
|---------------------------|---|
| TIRE SIZE | 340/55 - 16 |
| UM | IS STANDARD |
| CONSTRUCTION | |
| MACHINERY | BALER / IMPLEMENT MACHINERY / TRAILER / HARVESTER / IMPLEMENTS |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 121 A8 |
| LI/SS FREE ROLLING | 133 A8 |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 343 | RIM REC | 11.0 |
| OD (MM) | 785 | ECE | E11-106R-006421 |
| SLR (MM) | 358 | | |
| RC (MM) | 2358 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 3.20 |
|------------|------|
| 10 FR | 2885 |
| 25 FR | 2450 |
| 30 FR | 2305 |
| 40 FR | 2060 |
| 10 DW | 2030 |
| 25 DW | 1725 |
| 30 DW | 1625 |
| 40 DW | 1450 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.