


RIDEMAX FL 693 M



TIRE SIZE	600/60 R 30.5
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	CISTERNA MÓVEL / REBOQUE / IMPLEMENTOS AGRÍCOLAS
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS	169 D

DIMENSÕES IS STANDARD

SW (MM)	605	RIM REC	AG 20.00
OD (MM)	1495	RIM ALT	AG 18.00
SLR (MM)	681	ECE	E11-106R-006160
RC (MM)	4495	SRI	725

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1930	2165	2695	3065	3540	4015	4385	4805	5280
65	2120	2380	2960	3365	3890	4410	4815	5280	5800
50	2565	2880	3585	4075	4705	5340	5830	6390	7020
40	2880	3235	4025	4580	5290	6000	6550	7180	7890
30	3200	3595	4470	5085	5870	6660	7275	7975	8760
25	3350	3760	4675	5320	6145	6970	7610	8345	9165
10	3815	4285	5325	6060	6995	7935	8670	9505	10440

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.