DATA SHEET

Latest update
2-06-2026

AGRIMAX SIRIO

TIRE SIZE	**710/70 R 38**
UM	US STANDARD
CONSTRUCTION	
MACHINERY	HIGH-POWER TRACTOR / TRACTOR
VERSION	HIGH SPEED
TL/TT	TL
LI/SS	171 D ; 168 E

DIMENSIONS US STANDARD

USA CODE	94044283	**RC (IN)**	229.9
SW (IN)	28.2	**RIM REC**	DW 23 B
OD (IN)	77.1	**RIM ALT**	DW 25 B
SLR (IN)	34.9	**ECE**	E4-106R-000818

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	5810	6670	7660	8640	9630	10630	11490	12350
40	6380	7330	8410	9490	10580	11660	12610	13560
30	6700	7690	8840	9980	11110	12260	13250	14240
25	6990	8020	9210	10390	11580	12780	13810	14850
15	7560	8690	9960	11250	12540	13820	14950	16070
5	9570	10990	12610	14240	15870	17490	18910	20340

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..