


# FL 630 SUPER

	<b>600/55 R 22.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	YAYICI / TANKER / RÖMORK / UYGULAMALI MAKINE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
	162 D



## UNDEFINED US STANDARD

<b>USA CODE</b>	94056149	<b>RC (IN)</b>	147.9
<b>SW (IN)</b>	23.4	<b>RIM REC</b>	AG 20.00
<b>OD (IN)</b>	48.5	<b>ECE</b>	E11-106R-004759
<b>SLR (IN)</b>	22.0		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	15	17	23	29	35	41	46	52	58
45	3480	3910	4870	5530	6390	7250	7910	8690	9530
40	3820	4300	5350	6070	7020	7960	8700	9530	10470
30	4630	5200	6470	7350	8500	9630	10530	11540	12680
25	5200	5840	7260	8270	9550	10820	11830	12960	14240
15	6040	6790	8440	9600	11090	12580	13730	15060	16540
5	6890	7740	9620	10930	12630	14330	15650	17160	18850

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.