

AS 504

TIRE SIZE	12.5/80 - 18
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	135 A8
LI/SS FREE ROLLING	148 A8



РАЗМЕРЫ US STANDARD

USA CODE	94027262	RC (IN)	113.9
SW (IN)	12.1	RIM REC	W 9
OD (IN)	38.9	RIM ALT	9; 11
SLR (IN)	17.2	ECE	E11-106R-004347

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	71
5 FR	9720
15 FR	8270
20 FR	7780
25 FR	6940
5 DW	6720
15 DW	5720
20 DW	5380
25 DW	4810

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.