

AS 504

TIRE SIZE	6.00 - 16
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	STANDARD
TIRE TYPE	TT
LI/SS DRIVE WHEEL	83 A8
LI/SS FREE ROLLING	95 A8



РАЗМЕРЫ US STANDARD

USA CODE	94019168	RC (IN)	86.2
SW (IN)	6.5	RIM REC	4.00 E
OD (IN)	28.9	RIM ALT	4.50 E; 4½ K
SLR (IN)	13.5	ECE	E4-106R-002836

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	41
5 FR	2130
15 FR	1810
20 FR	1710
25 FR	1520
5 DW	1500
15 DW	1270
20 DW	1200
25 DW	1070

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.