

# TR 117

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | 11.2 - 24                                      |
| <b>UM</b>           | IS STANDARD                                    |
| <b>CONSTRUCTION</b> | ⊠ BIAS   |
| <b>MACHINERY</b>    | ROTTERANDE BEVATTNINGSMASKIN /<br>ARBETSFORDON |
| <b>VERSION</b>      | STANDARD                                       |
| <b>TIRE TYPE</b>    | TT   |
| <b>LI/SS</b>        | 110 A6   |



## DIMENSIONER IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 284  | <b>RIM REC</b> | W 10           |
| <b>OD (MM)</b>  | 1090 | <b>RIM ALT</b> | W 9            |
| <b>SLR (MM)</b> | 509  | <b>ECE</b>     | E4-106R-001967 |
| <b>RC (MM)</b>  | 3205 | <b>PR</b>      | 6              |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.80 | 2.35 |
|------------|------|------|
| 30         | 1060 | ---  |
| CREEP      | ---  | 2005 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.