


AGRIMAX SPARGO

| | |
|--------------|------------------------------------------------------------------------------------------|
| TIRE SIZE | VF 320/90 R 54 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRATTORE |
| VERSIONE | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 168 D |



DIMENSIONI IS STANDARD

| | | | |
|----------|------|---------|----------------------------|
| SW (MM) | 323 | RIM REC | W 11 |
| OD (MM) | 1948 | RIM ALT | W 10; DW 10; W 10 L; DW 11 |
| SLR (MM) | 910 | ECE | E11-106R-009070 |
| RC (MM) | 5946 | SRI | 925 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.0 | 1.2 | 1.4 | 1.6 | 1.8 | 2.0 | 2.2 | 2.4 | 2.6 | 2.8 | 3.0 | 3.2 | 3.4 | 3.6 | 3.8 | 4.0 | 4.2 | 4.4 |
|---------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| 70 | 2230 | 2490 | 2800 | 3060 | 3215 | 3370 | 3475 | 3575 | 3760 | 3940 | 4095 | 4250 | 4380 | 4510 | 4640 | 4770 | 4975 | 5180 |
| FROM 65 TO 40 | 2410 | 2690 | 3025 | 3305 | 3475 | 3640 | 3755 | 3865 | 4060 | 4260 | 4425 | 4595 | 4735 | 4875 | 5015 | 5155 | 5380 | 5600 |
| 30 | 2460 | 2745 | 3090 | 3375 | 3545 | 3715 | 3830 | 3945 | 4145 | 4345 | 4515 | 4690 | 4830 | 4975 | 5115 | 5260 | 5490 | 5715 |
| 20 | 2505 | 2800 | 3150 | 3440 | 3615 | 3790 | 3905 | 4020 | 4225 | 4430 | 4605 | 4780 | 4925 | 5070 | 5215 | 5360 | 5595 | 5825 |
| 10 | 2650 | 2960 | 3330 | 3635 | 3820 | 4005 | 4130 | 4255 | 4470 | 4685 | 4870 | 5055 | 5210 | 5360 | 5515 | 5670 | 5915 | 6160 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.