


# AS 504

<b>TIRE SIZE</b>	<b>420/55 - 17</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	LEVANTADOR TELESCÓPICO / REBOQUE PARA OS CAMPOS / IMPLEMENTOS AGRÍCOLAS / LEVANTADOR TELESCÓPICO
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	133 A8
<b>LI/SS FREE ROLLING</b>	145 A8



## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94032136	<b>RC (IN)</b>	106.8
<b>SW (IN)</b>	16.9	<b>RIM REC</b>	13.00
<b>OD (IN)</b>	35.8	<b>ECE</b>	E11-106R-003302
<b>SLR (IN)</b>	16.0	<b>PR</b>	16

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	33
5 FR	8950
15 FR	7610
20 FR	7160
25 FR	6390
5 DW	6360
15 DW	5400
20 DW	5080
25 DW	4540

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.