


# AGRIMAX ELOS

|                     |  |
|---------------------|--|
| <b>TYRE SIZE</b>    | <b>480/80 R 38</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | TRACTOR  |
| <b>VERSION</b>      | STANDARD   |
| <b>TL/TT</b>        | TL   |
| <b>LI/SS</b>        | 149 A8/B   |



## DIMENSIONS US STANDARD

|                 |          |                |                  |
|-----------------|----------|----------------|------------------|
| <b>USA CODE</b> | 94053766 | <b>RC (IN)</b> | 210.9            |
| <b>SW (IN)</b>  | 19.3     | <b>RIM REC</b> | W 16 L           |
| <b>OD (IN)</b>  | 71.0     | <b>RIM ALT</b> | W 15 L ; DW 16 L |
| <b>SLR (IN)</b> | 32.3     | <b>ECE</b>     | E11-106R-002991  |

## LOAD CAPACITY (LBS/TYRE)

| MPH / PSI   | 9    | 12   | 15   | 17   | 20   | 23   |
|-------------|------|------|------|------|------|------|
| <b>30</b>   | 3950 | 4590 | 5240 | 5870 | 6530 | 7160 |
| <b>25</b>   | 3950 | 4590 | 5240 | 5870 | 6530 | 7160 |
| <b>20</b>   | 4220 | 4920 | 5610 | 6290 | 6990 | 7670 |
| <b>5 LT</b> | 5290 | 6150 | 7010 | 7880 | 8740 | 9600 |
| <b>5 HT</b> | 4220 | 4920 | 5610 | 6290 | 6990 | 7670 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.