

AS 504

TIRE SIZE	7.50 - 16
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	HD
TIRE TYPE	TT
LI/SS DRIVE WHEEL	99 A8
LI/SS FREE ROLLING	112 A8



РАЗМЕРЫ US STANDARD

USA CODE	94043026	RC (IN)	97.4
SW (IN)	8.2	RIM REC	5.50 F
OD (IN)	31.6	RIM ALT	4.50 E; 5.00 F; 4.00 E; 5 K; 6 LB; 6.00 F
SLR (IN)	14.6	ECE	E11-106R-004337

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	46
5 FR	3460
15 FR	2940
20 FR	2770
25 FR	2470
5 DW	2390
15 DW	2030
20 DW	1920
25 DW	1710

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.