

# AT 171

|                  |                                    |
|------------------|------------------------------------|
| <b>TIRE SIZE</b> | <b>35X9 -20</b>                    |
| <b>UM</b>        | IS STANDARD                        |
| <b>MACHINERY</b> | ATV / MUD BOGGER TRACTOR / TRACTOR |
| <b>VERSION</b>   | STANDARD                           |
| <b>TL/TT</b>     | TT                                 |
| <b>LI/SS</b>     | 85 A8 ; 61 F                       |



## DIMENSIONS IS STANDARD

|                 |      |                 |      |
|-----------------|------|-----------------|------|
| <b>SW (MM)</b>  | 200  | <b>RIM REC</b>  | W 7  |
| <b>OD (MM)</b>  | 895  | <b>RIM ALT</b>  | W 6  |
| <b>SLR (MM)</b> | 419  | <b>PR</b>       | 6    |
| <b>RC (MM)</b>  | 2670 | <b>TRA CODE</b> | R1W+ |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR          | 1.40 | 1.00 |
|---------------------|------|------|
| 40 MUD BOGGING      | 515  | -    |
| 80 MUD BOGGING      | 257  | -    |
| 40 CASUAL TRANSPORT | -    | 425  |
| 80 CASUAL TRANSPORT | -    | 218  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.