


AGRIMAX RT 765

| | |
|---------------------|--|
| TYRE SIZE | 360/70 R 20 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | SPRAYER / TRACTOR / VINEYARD HARVESTER / HARVESTER / IMPLEMENTS |
| VERSION | STANDARD |
| TYRE TYPE | TL |
| LI/SS | 129 A8/B |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 357 | RIM REC | W 11 |
| OD (MM) | 1042 | RIM ALT | W 10; W 12 |
| SLR (MM) | 469 | ECE | E4-106R-000647 |
| RC (MM) | 3122 | SRI | 475 |

LOAD CAPACITY (KG/TYRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 |
|------------|------|------|------|------|------|------|------|------|
| 50 | 870 | 1000 | 1150 | 1295 | 1445 | 1595 | 1725 | 1850 |
| 40 | 870 | 1000 | 1150 | 1295 | 1445 | 1595 | 1725 | 1850 |
| 30 | 935 | 1070 | 1230 | 1390 | 1545 | 1705 | 1845 | 1980 |
| 10 LT | 1170 | 1340 | 1540 | 1740 | 1935 | 2135 | 2310 | 2480 |
| 10 HT | 935 | 1070 | 1230 | 1390 | 1545 | 1705 | 1845 | 1980 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.